

Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012

1. Identification of the substance/mixture and of the company/undertaking

Trade name	SaniAcetone	
Synonyms	Acetone, 2-propanone, Dimethyl ketone, Ketone propane, beta-Ketapropanone	
Product code	2110	
Use	Solvent, Industrial use	
Company	Sanichem(PTY) Ltd 141 Rochdale Rd Springfield Park Durban 4091	Emergency Telephone No +27 31 579 3222
Information (Product safety)	+27 31 579 3222 info@sanichem.co.za	
Emergency telephone number	Europe, Israel, Africa, Americas Middle East, Arabic African countries Asia Pacific China South Africa Australia	+44 (0)1235 239 670 +44 (0)1235 239 671 +65 3158 1074 +86 10 5100 3039 +27 (0)17 610 4444 +61 2 9032 0460

2. Hazards identification

Identification of the risks

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

3. Composition/information on ingredients

Acetone; Propan-2-one; Propanone

Contents: 100.00 %W/W

CAS-No. 67-64-1

Index-No. 606-001-00-8

EC-No. 200-662-2

Symbol(s) F, Xi

R-phrases(s) -R11 -R36 -R66 -R67

For the full text of the R-phrases mentioned in this Section, see Section 16.



Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012

4. First aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

5. Firefighting measures

Suitable extinguishing media	Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO ₂)
Extinguishing media which shall not be used for safety reasons	No information available.
Specific hazards during firefighting	Flash back possible over considerable distance.
Special protective equipment for firefighters	Wear self-contained breathing apparatus and protective suit.
Further information	Cool containers / tanks with water spray.

6. Accidental release measures

Personal precautions	Keep people away from and upwind of spill/leak. Remove all sources of ignition. Do not breathe vapours or spray mist.
Environmental precautions	Should not be released into the environment. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Soak up with inert absorbent material and dispose of as hazardous waste.



Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012

7. Handling and storage

Handling

Safe handling advice Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Take precautionary measures against static discharge. Ensure all equipment is electrically grounded before beginning transfer operations.

Advice on protection against fire and explosion Keep away from heat and sources of ignition. Use explosion-proof equipment.

Storage

Requirements for storage areas and containers Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Type	Control parameters	Update	Basis
ACETONE	TWA	1,780 mg/m ³	1995	South Africa RELs
	TWA	750 ppm	1995	South Africa RELs
	STEL	3,560 mg/m ³	1995	South Africa RELs
	STEL	1,500 ppm	1995	South Africa RELs

EUROPEAN OCCUPATIONAL EXPOSURE LIMITS

Components	Type	Control parameters	Update	Basis
ACETONE	TWA	1,210 mg/m ³	12 2009	EU Exposure Limit Values
	TWA	500 ppm	12 2009	EU Exposure Limit Values

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Gloves suitable for permanent contact:
Material: butyl-rubber
Break through time: 4 h
Material thickness: 0.5 mm



Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012

Eye protection	Safety glasses with side-shields
Skin and body protection	Protective suit, Safety shoes
Hygiene measures	Wash hands before breaks and immediately after handling the product.
Protective measures	Wear suitable protective equipment.

9. Physical and chemical properties

Form	Liquid
State of matter	Liquid
Colour	Colourless
Odour	Pungent
Melting point/range	-95.35 °C
Boiling point/boiling range	56.2 °C
Flash point	-20 °C
Autoignition temperature	465 °C
Lower explosion limit	2.6 %(V)
Upper explosion limit	12.8 %(V)
Vapour pressure	307.974 hPa; 25 °C
Density	0.79 g/cm ³
Water solubility	Soluble
Viscosity, kinematic	0.4 mm ² /s
Relative vapour density	2

10. Stability and reactivity

Materials to avoid	Strong oxidizing agents, Incompatible with acids., Halogenated compounds
Hazardous decomposition products	Carbon oxides
Hazardous reactions	Hazardous polymerisation does not occur.

11. Toxicological information

Acute oral toxicity	LD50 rat: 5,800 mg/kg; literature value
Acute inhalation toxicity	LC50 rat: > 20 mg/l; ; 4 h; literature value



Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012


Acute dermal toxicity	LD50 rabbit: 20,000 mg/kg; literature value
Skin irritation	rabbit: moderately irritating; (literature value)
Eye irritation	rabbit: irritating; (literature value)
	rabbit: moderately irritating; Draize Test
Sensitisation	No data available
Carcinogenicity	No data available
Reproductive toxicity	No toxicity to reproduction
Human experience: If inhaled	Vapours may cause drowsiness and dizziness.
Human experience: In case of skin contact	Repeated exposure may cause skin dryness or cracking
Human experience: In case of eye contact	Irritating to eyes

12. Ecological information

Biodegradability	100 %; 5 d
	89 %; 21 d
Bioaccumulation	1
Ecotoxicity effects	
Toxicity to fish	LC50 <i>Oncorhynchus mykiss</i> (rainbow trout): 5,540 mg/l; 96 h; literature value LC50 <i>Lepomis macrochirus</i> (Bluegill sunfish): 8,300 mg/l; 96 h; literature value LC50 <i>Pimephales promelas</i> : 8,120 mg/l; 96 h; literature value
Toxicity to daphnia and other aquatic invertebrates.	EC50 <i>Daphnia magna</i> : 10 mg/l; 24 h
Toxicity to algae	EC50 <i>Pseudokirchneriella subcapitata</i> : > 100 mg/l; 96 h; literature value

13. Disposal considerations

Product	In accordance with local and national regulations., Do not contaminate ponds, waterways or ditches with chemical or used container., The product should not be allowed to enter drains, water courses or the soil.
Contaminated packaging	Do not burn, or use a cutting torch on, the empty drum. Triple rinse containers., Can be offered for recycling, re-conditioning or puncture.



Safety Data Sheet

SaniAcetone

Version 1.13


Revision Date 29.03.2012

14. Transport information

ADR	UN number: 1090; Class: 3; Packaging group: II; F1; Description of the goods: ACETONE
RID	UN number: 1090; Class: 3; Packaging group: II; F1; Description of the goods: ACETONE
ADNR	UN number: 1090; Class: 3; Packaging group: II; F1; Description of the goods: ACETONE
IMDG	UN number: 1090; Class: 3; EmS: F-E, S-D; Packaging group: II; Description of the goods: ACETONE
ICAO/IATA	UN number: 1090; Class: 3; Packaging group: II; Description of the goods: Acetone

15. Regulatory information

Labelling



Regulatory base

67/548/EEC

Symbol(s)

F: Highly flammable
Xi: Irritant

R-phrases(s)


R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

S-phrases(s)

S 2: Keep out of the reach of children.
S 9: Keep container in a well-ventilated place.
S16: Keep away from sources of ignition - No smoking.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Hazardous components which must be listed on the label

Acetone; Propan-2-one; Propanone



Safety Data Sheet

SaniAcetone

Version 1.13

Revision Date 29.03.2012

16. Other information

Full text of R-phrases referred to under sections 2 and 3

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with ISO 11014 and ANSI Z400.1.1993. The SDS provides information regarding the health, safety and environmental hazards, at the date of issue, to facilitate the safe receipt, use and handling of the product in the workplace. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which the product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which the product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place as regards health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of the product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy or assume any liability for the incompleteness of the information contained herein or any advice given. The product is sold and risk passes in accordance with the specific terms and conditions of sale.

The MSDS was created by: F. SHAI

The MSDS was approved by: M. HUYSER